

Technology

Evaled vacuum evaporators are an effective fluid waste management solution for concentrating wastewater volumes, removing pollutant substances and producing high quality, reusable distillate (ZLD).

This industrial evaporation system is fully automatized. Modular units are low in energy consumption with low CO₂ footprint.



watch the video

EVALED is a registered trademark. All rights reserved.

For more information visit our website www.evaled.com

Benefits

disposal cost reduction

wastewater volume reduction

high quality outlet for recycling and reuse

by-products recovery

ZLD (Zero Liquid Discharge)

Specifications

skid-mounted modular units

highly automated, 24/7 operation

ready to use (Plug & Play)

monitoring by remote control

minimum maintenance

quality certification ISO 9001/2015

Reliability

All evaporators undergo a Factory Acceptance Test (FAT) with water before shipment.

EVALED

An effective ready-to-market solution for concentrating and removing salts, heavy metals and a variety of hazardous components.



KEYWORDS

Reliability, effectiveness in wastewater volume reduction, high quality distillate, water reuse (ZLD).

EVALED

Three different evaporation technologies operating in under vacuum close loop systems to meet your water treatment needs.

SERIES

Heat pumb




specifications

Designed to offer flexibility and superior reliability

- · low boiling temperature
- · recovery of heat- sensitive products
- · good distillate quality
- · low fouling and scaling





Ideal when waste thermal energy and cold water are available on site (cogeneration)

- · high concentration levels
- available in single and multiple effect
- engineered to work in either continuous or batch mode





Engineered for the treatment of large wastewater flowrates

- · very low energy consumption
- · high efficiency

Wastewater treatment units with distillate production capacities from 0.1 to 120 m³/day (0.02 - 22 gpm).

MODELS							m³/day	
F	0.7	1.4	2.4	4	6	8	12	24
 R	150 (I/day)	0.5	1	2				
 F	20	40	60					
R/S	3	6	12					,,,,,,
F	12	15	25	40	60	120		
N	6							



Industries and applications

Mechanical & Surface Treatments (Automotive, Aviation, Appliances, Furniture)

Healthcare (Pharma, Cosmetics)

Chemicals & Detergents

Waste (Incineration, Landfill, Collectors)

Biogas & Biofuels

Photovoltaic & Microelectronics

Food & Beverage

Graphic Arts

Power

Oil & Gas

Mining & Primary Metals

Other industrial processes (Textile, Pulp & Paper, etc.)











Veolia Water Technologies Italia has a firm commitment to reduce the CO₂ emissions of its technological offer. Careful analysis enable to calculate the CO₂ emissions of EVALED solutions.

Contact us for a customized Carbon Footprint Assessment. www.evaled.com

Service Optional

EVA life

The program which makes your unit perfectly performing for its entire life.

Hubgrade

EVA Link Remote Monitoring



EVA Clean Automatic Washing System

EVA Lab Analysis

EVA Time Warranty Extension

EVA Heart Blower Maintenance

EVA Parts Spare parts ready from stock

EVA Maintenance Regular Service Pack

EVA Top Full Service Pack

Fit-for-purpose materials

The ultimate manufacturing materials to treat even the most aggressive effluents

Veolia has worked together with renowned materials research centers in order to select the most suitable materials to safely treat aggressive liquids.

Resistance to corrosion is a strong feature of every Evaled evaporator, essential when dealing with extremely concentrated liquids.

Austenic stainless steel

Austenic weakly bound structure, non-hardening, non-magnetic. The low percentage of carbon in this alloy reduces the risk of intergranular corrosion at high temperatures.

Uses: alkaline liquids, acid liquids (pH>5) with a low percentage of chlorides (e.g., oil emulsions, liquids from flexographic printing).

Superduplex stainless steel

Austenic-ferritic structure, magnetic.

The high percentage of chromium gives excellent resistance to localized corrosion.

Uses: acidic liquids (pH>4) with high chlorides and metals content (e.g., galvanic wastewater, landfill leachate).

Nickel alloy

High flexibility Cr-Ni-Mo steel.

The low carbon content ensures resistance to the formation of carbides when zones are exposed to thermal variation. It has excellent resistance to localized corrosion, both in oxidizing and reducing environments, even at high temperatures.

Uses: very acid liquids (pH<3) with high content of chlorides, fluorides and metal (e.g., anodizing wastewater, special applications).

Silicon Carbide (SiC)

PC type only (KT-Series)

Chemically inert material resistant to almost all agressive substances. It is usually matched with another chemically inert material, PTFE, a fluoride co-polymer used for coating the inner surfaces of the boiling chamber.

Uses: aggressive liquids (e.g., pickling wastewater, chromic acid recovery).

Resourcing the world